



WP-T610



SDS100


As Internet usage continues to become more mobile, customers have an increasing expectation for wireless Internet access at public locations, such as in coffee shops, restaurants, hotel lobbies, convention centers or airport terminals.

Whether you are thinking of running a hotspot for free or for a fee, you will need a hotspot management system to maintain quality of service for your customers, eliminate free-riders, and keep your network secure. 4ipnet **Hotspot Network Ticket Generator Combo Set**,


SDS100 Smart Device Server and WP-T610 POS Printer, is able to provide the easy hotspot solution that turns your venue instantly into a managed, branded and moneymaking hotspot.

4ipnet **Hotspot Network Ticket Generator Combo Set** leads a simpler way to serve the hotspot area. Designed to support account generation, **SDS100 Smart Device Server** triggers the built-in On-Demand billing plan(s) inside **4ipnet WHG Controllers or HSG Gateways** and then prints account tickets with **WP-T610 POS Printer**. Each WHG Controller or HSG Gateway can simultaneously support multiple Ticket Generator Combo Sets via the network.

The on-demand accounts can be generated at the counter by the hotspot owner with just a few clicks on the SDS100 Smart Device Server to print account tickets. All WP-T610 POS Printers connect directly to SDS100 Smart Device Server with serial port (in RS-232) and SDS100 has a standard TCP/IP (in RJ-45) interface, so it is easy for **Hotspot Network Ticket Generator Combo Set** to join your network!



Small-size Hotspot Network



Medium to Larger-scale Hotspot Network




Diagram of SDS100 Connecting to WP-T610 and WHG Controller

SPECIFICATIONS

SDS100 Smart Device Server



- Number of Ethernet Ports: 1 in RJ-45
- Speed: 10/100 Mbps
- Number of Serial Ports: 2
- Serial Standards: RS-232 DB-9M
- Baud rate: 9600 bps
- Configuration Options: Web Console
- Weight: 300 g
- Dimensions Without Mounting Kit: 90 x 123 x 27 mm
- Dimensions With Mounting Kit: 116 x 123 x 27 mm
- Input Voltage: 12 to 48 VDC
- Power Consumption: 200 mA @ 12 V, 106 mA @ 24 V

WP-T610 POS Printer



- Print Method: Thermal Line Printing
- Print Speed: 60 mm/sec
- Resolution: 203 dpi
- Paper Width: 57.5±0.5 mm x 80 (max) mm
- Interface: Serial (RS-232C)
- Character:
 - (1) Font A: 12*24 dots
 - (2) Chinese: 24*24 dots
- Power Supply: 10 VDC / 3A
- Operating Temperature: 0°C ~ +45°C
- Storage Temperature: -10°C ~ +50°C
- Dimension: 196mm(D) x 126mm(W) x 118mm(H)
- Weight: 2.10kg